

The **Best** Filters Begin With The **Best** Media

Specialty Collection Bags

Overspray Collection Bags

Fiber Bond's collection bags are designed for heavy-duty paint and powder coating overspray applications. The additional media in the filter's tapered pockets increase the usable surface area and reduce resistance. Sturdy 9-gauge wire supports provide a tight, self-sealing fit. Header-style models are available for metal frame applications.

Extended Surface Area • Maximum Efficiency • Less Downtime

NESHAP Compliant • EPA Test Method 319

EP GXG Bag High-Efficiency Overspray Collection

The E. P. GXG Bag consists of two-layers of media, a dual-density E. P. Green upstream layer and a layer of high-density polyester. When used as a final filter, the GXG Bag meets EPA 319 compliance standards for 2-stage systems.

NESHAP Compliant • EPA 319 • 2-Stage

UltraStop Bag Ultra-Efficient Overspray Collection

The heat-sealed, six-pocket UltraStop Bag provides the highest efficiency for overspray collection. It exceeds 90% efficiency in removing one-micron particles. The design keeps the pockets erect, delivering full-surface filtering.


NESHAP Compliant • EPA 319 • 3-Stage



EP GXP Bag Powder Overspray Collection

The two-layer E. P. GXP Bag combines dual-density E. P. Green media with a layer of high-efficiency, fine-denier polyester. This heavy duty bag is ideal for powder overspray collection in non-recovery booths. Filter is reusable.





110 Menke Road, Michigan City, IN 46360 • Phone (219) 879-4541 • Fax (219) 874-7502 Email: customer.service@fiberbond.net • www.fiberbond.net



The **Best** Filters Begin With The **Best** Media

Specialty Collection Bags

Test Results • EPA Test Method 319

Independent Test Results • EPA 319 EP GXG Bag 2-Stage Filtration

	Minimum Efficiency	Results
Solid Phase	10% of 2.60 micron particles	33%
	50% of 5.00 micron particles	81%
	90% of 8.10 micron particles	97%
Liquid Phase	10% of 2.20 micron particles	30%
	50% of 4.10 micron particles	88%
	90% of 5.70 micron particles	98%



Independent Test Results • EPA 319 UltraStop Bag 3-Stage Filtration

	Minimum Efficiency	Results
Solid	75% of 0.70 micron particles	80.5%
Phase	85% of 1.10 micron particles	91%
	95% of 2.50 micron particles	96.2%
Liquid	65% of 0.42 micron particles	66.8%
Phase	80% of 1.00 micron particles	84.2%
	95% of 2.00 micron particles	95.3%





3-Stage System EP White Pad EP Green Bag UltraStop Bag



EP Collection Bags test report is available by contacting Fiber Bond at (219) 879-4541.



110 Menke Road, Michigan City, IN 46360 • Phone (219) 879-4541 • Fax (219) 874-7502 Email: customer.service@fiberbond.net • www.fiberbond.net • November 2014